

0625-E

6.5" TFT LCD, 1000 nits LED backlight, 640x480



Key Features



Sunlight Readable



Wide Temp.



Low Power Consumption



MTBF

70,000 Hrs

MTBF

- 6.5" sunlight readable, high brightness (1,000 nits)
- Resolutions: 640 x 480
- Industry leading LED backlight
- Aspect ratio of 4:3
- Wide temperature (-30°C~80°C)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF0625-E	DLH0625-E	SLD0625-E
Description	6.5" TFT LCD, 1000 nits LED backlight, 640x480		
Screen size	6.5"		
Display area (mm)	132.4(H) x 99.3(V)		
Brightness	1000 cd/m ²		
Resolution	640x480		
Aspect ratio	4:3		
Contrast ratio	600:1		
Pixel pitch (mm)	0.207 (H) x 0.207 (V)		
Pixel per inch (PPI)	123		
Viewing angle	160° (H), 140° (V)		
Color saturation (NTSC)	55%		
Display colors	16.2M		
Response time (Typical)	25ms		
Video interface	LVDS	VGA, DVI-D	
Input power		DC 12V	
Power consumption	3.9w	5w	
Dimensions (mm)	153x118x10.9	153x118x10.9	172.2x130.2x33.5
Bezel size (U/B/L/R)	7.2/8/4.95/6.15	7.2/8/4.95/6.15	14.6/14.6/19.1/19.1
Weight (Net)	0.2kg	0.3kg	0.72kg
Mounting			VESA 75x75
OSD key		4 keys (Power switch, menu, +, -)	
OSD control		Brightness, color, contrast, H/V position... etc	
Operating temperature	-30°C ~ +80°C		
Storage temperature	-30°C ~ +80°C		
Product approval			CE, FCC

Ordering Information

DLF0625-ENN-A01	6.5",1000nits,VGA,5IN1,V01
DLH0625-ENN-I01	6.5",1000nits,VGA,AD6038GD.DC12V,3 in 1,V1
SLD0625-ENB-I01	6.5",1000nits,VGA,AD6038DM.O/B,5 in 1,V1