

# 0765-I

7" TFT LCD, 1000 nits LED backlight, 1024x600



Sunlight Readable



Wide Temp.



Low Power Consumption



MTBF  
70,000 Hrs

## Key Features

- 7" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1024 x 600
- Industry leading LED backlight
- Aspect ratio of 16:9
- Wide temperature (-20°C~70°C)
- Low power consumption
- BL MTBF: 70,000 hours

## Specifications

	DLF0765-I	DLH0765-I	SLO0765-I	SLD0765-I
Description	7" TFT LCD, 1000 nits LED backlight, 1024x600			
Screen size	7"			
Display area (mm)	154.2(H) x 85.9(V)			
Brightness	1000 cd/m <sup>2</sup>			
Resolution	1024x600			
Aspect ratio	16:9			
Contrast ratio	900:1			
Pixel pitch (mm)	0.1506 (H) x 0.1432 (V)			
Pixel per inch (PPI)	170			
Viewing angle	150° (H), 145° (V)			
Color saturation (NTSC)	81%			
Display colors	16.7M			
Response time (Typical)	25ms			
Video interface	LVDS	VGA, DVI-D, HDMI		
Input power		DC 12V		
Power consumption	4.5w	7.8w		
Dimensions (mm)	164.9x100x4.8	164.9x100x4.8	220.4x128.4x41.5	190.4x128.4x41.5
Bezel size (U/B/L/R)	3.08/7.43/2.35/5.3	3.08/7.43/2.35/5.3	18.88/22.03/17.7/17.49	18.88/22.03/17.7/17.49
Weight (Net)	0.15kg	0.25kg	1kg	0.86kg
Mounting			VESA 75x75	VESA 75x75
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	-20°C ~ +70°C			
Storage temperature	-30°C ~ +80°C			
Product approval				CE, FCC

## Ordering Information

DLF0765-INN-A01	7",1000nits,1024*600,LID7B.10 in 1,V1
DLH0765-INN-G01	7",1000nits,1024*600,LID7B.AD2662GDHM,10 in 1,V1
SLO0765-INB-G01	7",1000nits,1024*600,LID7B.AD2662GDHM,O/B,DC12V,5in1,V1
SLD0765-INB-G01	7",1000nits,1024*600,LID7B.AD2662GDHM,O/B,DC12V,5in1,V1