


0868-E

8.4" TFT LCD, 1600 nits LED backlight, 800x600



Sunlight Readable



Wide Temp.



Low Power Consumption



MTBF
70,000 Hrs

Key Features

- 8.4" sunlight readable, high brightness (1,600 nits)
- Resolutions: 800 x 600
- Industry leading LED backlight
- Aspect ratio of 4:3
- Wide temperature (-20°C~70°C)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF0868-E	DLH0868-E	SLO0868-E	SLD0868-E
Description	8.4" TFT LCD, 1600 nits LED backlight, 800x600			
Screen size	8.4"			
Display area (mm)	170.4(H) x 127.8(V)			
Brightness	1600 cd/m ²			
Resolution	800x600			
Aspect ratio	4:3			
Contrast ratio	600:1			
Pixel pitch (mm)	0.213 (H) x 0.213 (V)			
Pixel per inch (PPI)	119			
Viewing angle	160° (H), 140° (V)			
Color saturation (NTSC)	60%			
Display colors	16.2M			
Response time (Typical)	35ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	6.8w	10w		
Dimensions (mm)	203x142.5x5.7	203x142.5x5.7	253x153.2x43.6	227x153.2x43.5
Bezel size (U/B/L/R)	6.25/5.05/18.33/10.87	6.25/5.05/18.33/10.87	11.9/11.9/27.5/27.5	11.9/11.9/27.5/27.5
Weight (Net)	0.2kg	0.3kg	1.3kg	1.25kg
Mounting			VESA 75x75	VESA 75x75
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	-20°C ~ +70°C			
Storage temperature	-20°C ~ +70°C			
Product approval				CE, FCC

Ordering Information

DLF0868-ENN-A01	8.4",1600nits,SVGA,LID08A06.V01(10 in 1)
DLH0868-ENN-I01	8.4",1600nits,SVGA,LID08.AD6038GD,DC 12V input.V01(10 in 1)
SLO0868-ENB-I01	8.4",1600nits,SVGA,LID08A.AD6038GD,O/B,DC 12V,V01
SLD0868-ENB-I01	8.4",1600nits,SVGA,LID08A.AD6038GD,O/B,DC 12V,V01