


1015-I



10.1" TFT LCD, 1000 nits LED backlight, 1280x800



Key Features

- 10.1" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1280 x 800
- Industry leading LED backlight
- Aspect ratio of 16:9
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF1015-I	DLH1015-I		
Description	10.1" TFT LCD, 1000 nits LED backlight, 1280x800			
Screen size	10.1"			
Display area (mm)	216.9(H) x 135.6(V)			
Brightness	1000 cd/m ²			
Resolution	1280x800			
Aspect ratio	16:10			
Contrast ratio	900:1			
Pixel pitch (mm)	0.1695 (H) x 0.1695 (V)			
Pixel per inch (PPI)	149			
Viewing angle	170° (H), 170° (V)			
Color saturation (NTSC)	53%			
Display colors	16.7M			
Response time (Typical)	25ms			
Video interface	LVDS	VGA, DVI-D, HDMI		
Input power		DC 12V		
Power consumption	6w	11w		
Dimensions (mm)	229.5x151.1x4.23	229.5x151.1x4.23		
Bezel size (U/B/L/R)	6.27/6.73/4.47/5.57	6.27/6.73/4.47/5.57		
Weight (Net)	0.15kg	0.15kg		
Mounting				
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	0°C ~ +50°C			
Storage temperature	-20°C ~ +60°C			
Product approval				

Ordering Information

DLF1015-INN-A01	10.1",1000nits,1280*800.w/LVDS & LID Converter board.10 in 1,V01
DLH1015-INN-I01	10.1",1000nits,1280*800.AD6038GA.w/LVDS & LID Converter board.DC 12V,V01
DLH1015-INN-G01	10.1",1000nits,1280*800.AD2662GDHM,DC12V,V01