


# 1015-V

10.1" TFT LCD, 1000 nits LED backlight, 1024x600



Sunlight Readable



Wide Temp.



Low Power Consumption



MTBF  
70,000 Hrs

## Key Features

- 10.1" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1024 x 600
- Industry leading LED backlight
- Aspect ratio of 16:9
- Wide temperature (-20°C~70°C)
- Low power consumption
- BL MTBF: 70,000 hours

## Specifications

	DLF1015-V	DLH1015-V	DLO1015-V	DLD1015-V
Description	10.1" TFT LCD, 1000 nits LED backlight, 1024x600			
Screen size	10.1"			
Display area (mm)	222.7(H) x 125.3(V)			
Brightness	1000 cd/m <sup>2</sup>			
Resolution	1024x600			
Aspect ratio	16:9			
Contrast ratio	900:1			
Pixel pitch (mm)	0.2175 (H) x 0.2088 (V)			
Pixel per inch (PPI)	117			
Viewing angle	160° (H), 160° (V)			
Color saturation (NTSC)	49%			
Display colors	16.7M			
Response time (Typical)	16ms			
Video interface	LVDS	VGA		
Input power		DC 12V		
Power consumption	4.5w	6.36w		
Dimensions (mm)	235x143x7.54	235x143x7.54	274x148.2x37	244x148.2x36.5
Bezel size (U/B/L/R)	7.36/7.36/3.74/5.54	7.36/7.36/3.74/5.54	10.95/10.95/10.2/10.2	10.95/10.95/10.2/10.2
Weight (Net)	0.3kg	0.3kg	0.8kg	0.7kg
Mounting			VESA 50x50	VESA 50x50
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	-20°C ~ +70°C			
Storage temperature	-30°C ~ +80°C			
Product approval			CE, FCC	CE, FCC

## Ordering Information

DLF1015-VNN-A01	10.1",1000nits,1024*600.LID10A,V01(5 in 1)
DLH1015-VNN-I01	10.1",1000nits,1024*600,LID10A.AD6038GA,DC12V,V01(5 in 1)
DLO1015-VNB-I01	10.1",1000nits,1024*600,LID10A.AD6038GA,O/B,DC 12V,V01
DLD1015-VNB-I01	10.1",1000nits,1024*600,LID10A.AD6038GA,O/B,DC 12V,V01