

1055-E

10.4" TFT LCD, 1000 nits LED backlight, 1024x768



Sunlight Readable



Wide Viewing Angle



Wide Temp.



MTBF
70,000 Hrs

Key Features

- 10.4" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1024 x 768
- Industry leading LED backlight
- Wide viewing angel of 176° (H), 176° (V)
- Wide temperature (-30°C~70°C)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF1055-E	DLH1055-E	SLO1055-E	SLD1055-E
Description	10.4" TFT LCD, 1000 nits LED backlight, 1024x768			
Screen size	10.4"			
Display area (mm)	210.4(H) x 157.8(V)			
Brightness	1000 cd/m ²			
Resolution	1024x768			
Aspect ratio	4:3			
Contrast ratio	800:1			
Pixel pitch (mm)	0.2055 (H) x 0.2055 (V)			
Pixel per inch (PPI)	123			
Viewing angle	176° (H), 176° (V)			
Color saturation (NTSC)	65%			
Display colors	16.2M			
Response time (Typical)	40ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	12w	16w		
Dimensions (mm)	225.2x176.3x8.7	225.2x176.3x8.7	340x228x57	311x202x57
Bezel size (U/B/L/R)	8/6.5/5.7/4.4	8/6.5/5.7/4.4	34.3/34.3/63.9/63.9	21.3/21.3/49.4/49.4
Weight (Net)	0.29kg	0.29kg	2.2kg	2.71kg
Mounting			VESA 75x75	VESA 75x75
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	-30°C ~ +70°C			
Storage temperature	-30°C ~ +80°C			
Product approval			CE, FCC	CE, FCC

Ordering Information

DLF1055-ENN-A11	10.4",1000nits,XGA,LID10A05.5 in 1,V2
DLH1055-ENN-I11	10.4",1000nits,XGA,LID10A05.AD6038GD,5 in 1,DC 12V,V2
SLO1055-ENA-I11	10.4",1000nits,XGA,LID10A05.AD6038GD,O/B,DC 12V,input,V2
SLD1055-ENA-I11	10.4",1000nits,XGA,LID10A05.AD6038GD,O/F,DC 12V,input,V2