


1068-E

10.4" TFT LCD, 1600/2000 nits LED backlight, 800x600



Sunlight Readable



Wide Temp.



Low Power Consumption



MTBF
70,000 Hrs

Key Features

- 10.4" sunlight readable, high brightness (1,600/2,000 nits)
- Resolutions: 800 x 600
- Industry leading LED backlight
- Aspect ratio of 4:3
- Wide temperature (-20°C~70°C)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF1068-E	DLH1068-E	SLO1068-E	SLD1068-E
Description	10.4" TFT LCD, 1600/2000 nits LED backlight, 800x600			
Screen size	10.4"			
Display area (mm)	210.2(H) x 158.4(V)			
Brightness	1600/2000 cd/m ²			
Resolution	800x600			
Aspect ratio	4:3			
Contrast ratio	400:1			
Pixel pitch (mm)	0.264 (H) x 0.264 (V)			
Pixel per inch (PPI)	96			
Viewing angle	130° (H), 110° (V)			
Color saturation (NTSC)	55%			
Display colors	262K			
Response time (Typical)	25ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	5.7w	10.3w		
Dimensions (mm)	236x176.9x6.3	236x176.9x6.3	279x204x45	249.2x206.2x45.8
Bezel size (U/B/L/R)	6.3/8.65/11.5/9.5	6.3/8.65/11.5/9.5	10.1/31.9/32/32	12.2/33.9/17.85/17.85
Weight (Net)	0.3kg	0.8kg	1.3kg	1.64kg
Mounting			VESA 75x75	VESA 75x75
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	-20°C ~ +70°C			
Storage temperature	-30°C ~ +80°C			
Product approval			CE, FCC	CE, FCC

Ordering Information

DLF1068-ENN-A01	10.4",1600nits,SVGA,LID10A09,V01(5 in 1)
DLH1068-ENN-I01	10.4",1600nits,SVGA,LID10A09.AD6038GA,LS,5 in 1,V01
SLO1068-EGA-I01	10.4",1600nits,SVGA,LID10A09.AD6038GD,O/F,DC12V,V01
SLD1068-EGA-I01	10.4",1600nits,SVGA,LID10A09.AD6038GD,O/F,DC12V,V01