


1268-E

12.1" TFT LCD, 1600/2000 nits LED backlight, 1024x768



Sunlight Readable



Wide Temp.



Low Power Consumption



MTBF 70,000 Hrs

Key Features

- 12.1" sunlight readable, high brightness (1,600/2,000 nits)
- Resolutions: 1024 x 768
- Industry leading LED backlight
- Aspect ratio of 4:3
- Wide temperature (-30°C~85°C)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF1268-E	DLH1268-E	SLO1268-E	SLD1268-E
Description	12.1" TFT LCD, 1600/2000 nits LED backlight, 1024x768			
Screen size	12.1"			
Display area (mm)	245.7(H) x 184.3(V)			
Brightness	1600/2000 cd/m ²			
Resolution	1024x768			
Aspect ratio	4:3			
Contrast ratio	700:1			
Pixel pitch (mm)	0.24 (H) x 0.24 (V)			
Pixel per inch (PPI)	106			
Viewing angle	160° (H), 160° (V)			
Color saturation (NTSC)	80%			
Display colors	16.2M			
Response time (Typical)	35ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	10w	12.5w		
Dimensions (mm)	272x204.6x12.5	272x204.6x12.5	293.6x205.6x36.7	272x205.4x36.2
Bezel size (U/B/L/R)	8.3/8.3/12.4/10.6	8.3/8.3/12.4/10.6	9.1/8.3/23.4/21.6	9.1/8.3/12.4/10.6
Weight (Net)	0.5kg	0.6kg	1.35kg	1.3kg
Mounting			VESA 75x75	VESA 75x75
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	-30°C ~ +85°C			
Storage temperature	-30°C ~ +85°C			
Product approval			CE, FCC	CE, FCC

Ordering Information

DLF1268-ENN-A21	12",1600nits,XGA,LID12A.DC 12V,w/o boss,5 in 1,V03
DLH1268-ENN-I21	12",1600nits,XGA,LID12A.AD6038GD,DC 12V,w/o boss.5 in 1,V03
SLO1268-ENB-I21	12",1600nits,XGA,LID12A.AD6038GD,O/B,DC 12V,2 in 1,V03
SLD1268-ENB-I21	12",1600nits,XGA,LID12A.AD6038GD,O/B,DC 12V,2 in 1,V03