


1315-E

13.3" TFT LCD, 1000 nits LED backlight, 1280x800



Sunlight Readable



Wide Temp.



Low Power Consumption



MTBF
70,000 Hrs

Key Features

- 13.3" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1280 x 800
- Industry leading LED backlight
- Aspect ratio of 16:10
- Wide temperature (-20°C~70°C)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF1315-E	DLH1315-E	SLO1315-E	SLD1315-E
Description	13.3" TFT LCD, 1000 nits LED backlight, 1280x800			
Screen size	13.3"			
Display area (mm)	286.08(H) x 178.8(V)			
Brightness	1000 cd/m ²			
Resolution	1280x800			
Aspect ratio	16:10			
Contrast ratio	800:1			
Pixel pitch (mm)	0.2235 (H) x 0.2235 (V)			
Pixel per inch (PPI)	113			
Viewing angle	140° (H), 120° (V)			
Color saturation (NTSC)	37%			
Display colors	16.2M			
Response time (Typical)	16ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	7.5w	12.5w		
Dimensions (mm)	299x195x7.7	299x195x7.7	343.6x270x55	343.6x270.8x56.6
Bezel size (U/B/L/R)	8.2/7/5.5/4.4	8.2/7/5.5/4.4	29.1/60/27.2/27.2	30.1/60.5/28/28
Weight (Net)	0.75kg	0.85kg	2.5kg	2.81kg
Mounting			VESA 75x75	VESA 75x75
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	-20°C ~ +70°C			
Storage temperature	-30°C ~ +80°C			
Product approval			CE, FCC	CE, FCC

Ordering Information

DLF1315-ENN-A05	13.3",1000nits,WXGA,LID13A.5 in 1,V01
DLH1315-ENN-I01	13.3",1000nits,WXGA,LID13A.AD6038GD,5 in 1,V01
SLO1315-ENB-I01	13.3",1000nits,WXGA,O/B.LID13A03,AD6038GD,DC 12V V01
SLD1315-ENA-I01	13.3",1000nits,WXGA,LID13A.AD6038GD,O/F,DC 12V,V01