

1506-S

15" TFT LCD, 1000 nits LED backlight, 1024x768



Sunlight Readable



High Contrast



Wide Temp.



MTBF
70,000 Hrs

Key Features

- 15" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1024 x 768
- Industry leading LED backlight
- High color contrast ratio (1700:1)
- Wide temperature range (-20°C~70°C)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF1506-S	DLH1506-S	DLO1506-S	DLD1506-S
Description	15" TFT LCD, 1000 nits LED backlight, 1024x768			
Screen size	15"			
Display area (mm)	304.1(H) x 228.1(V)			
Brightness	1000 cd/m ²			
Resolution	1024x768			
Aspect ratio	4:3			
Contrast ratio	1700:1			
Pixel pitch (mm)	0.297 (H) x 0.297 (V)			
Pixel per inch (PPI)	85			
Viewing angle	170° (H), 170° (V)			
Color saturation (NTSC)	70%			
Display colors	16.7M			
Response time (Typical)	35ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	13w	17w		
Dimensions (mm)	326.5x253.5x9.5	326.5x253.5x9.5	389x325x60.1	389x325x61.6
Bezel size (U/B/L/R)	11.1/11.1/9.6/9.6	11.1/11.1/9.6/9.6	11.1/11.1/9.6/9.6	11.1/11.1/9.6/9.6
Weight (Net)	1kg	1.1kg	3.8kg	4kg
Mounting			VESA 75x75	VESA 75x75
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	-20°C ~ +70°C			
Storage temperature	-20°C ~ +70°C			
Product approval			CE, FCC	CE, FCC

Ordering Information

DLF1506-SNN-A02	15",1000nits,XGA,LID15B,5 in 1.V01
DLH1506-SNN-I02	15",1000nits,XGA,LID15B.AD6038GD,DC12V,5 in 1,V01
DLO1506-SNB-I01	15",1000nits,XGA,LID15B.AD6038GD,O/B,DC12V,1 in 1.V01
DLD1506-SNA-I01	15",1000nits,XGA,LID15B.AD6038GD,O/F,DC12V,1 in 1.V01