

1555-E

15" TFT LCD, 1000 nits LED backlight, 1024x768



Sunlight Readable



Low Power Consumption



Wide Temp.



MTBF
70,000 Hrs

Key Features

- 15" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1024 x 768
- Industry leading LED backlight
- High contrast ratio (1000:1)
- Wide temperature (-30°C~80°C)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF1555-E	DLH1555-E	SLO1555-E	SLD1555-E
Description	15" TFT LCD, 1000 nits LED backlight, 1024x768			
Screen size	15"			
Display area (mm)	304.1(H) x 228.1(V)			
Brightness	1000 cd/m ²			
Resolution	1024x768			
Aspect ratio	4:3			
Contrast ratio	1000:1			
Pixel pitch (mm)	0.297 (H) x 0.297 (V)			
Pixel per inch (PPI)	85			
Viewing angle	160° (H), 140° (V)			
Color saturation (NTSC)	60%			
Display colors	16.2M			
Response time (Typical)	16ms			
Video interface	LVDS	VGA		
Input power		DC 12V		
Power consumption	13w	16w		
Dimensions (mm)	326.5x253.5x11.6	326.5x253.5x11.6	389x325x60.1	389x325x61.6
Bezel size (U/B/L/R)	11.1/11.1/9.6/9.6	11.1/11.1/9.6/9.6	11.1/11.1/9.6/9.6	11.1/11.1/9.6/9.6
Weight (Net)	1.33kg	1.43kg	3.83kg	4.62kg
Mounting			VESA 75x75	VESA 75x75
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	-30°C ~ +80°C			
Storage temperature	-40°C ~ +85°C			
Product approval			CE, FCC	CE, FCC

Ordering Information

DLF1555-ENN-A12	15",1000nits,XGA,LID15A11.V2(5 in 1)
DLH1555-ENN-I12	15",1000nits,XGA,LID15A11.AD6038GA,V2
SLO1555-ENB-I11	15".1000nits,XGA,LID15A11.AD6038G,O/B,V2
SLD1555-ENA-I11	15",1000nits,XGA,LID15A11.AD6038G,O/F,V2