

1568-E

15" TFT LCD, 1600 nits LED backlight, 1024x768



Sunlight Readable



Low Power Consumption



Wide Temp.



MTBF 70,000 Hrs

Key Features

- 15" sunlight readable, high brightness (1,600/2,000 nits)
- Resolutions: 1024 x 768
- Industry leading LED backlight
- High contrast ratio (1000:1)
- Wide temperature range (-20°C~70°C)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF1568-E	DLH1568-E	SLO1568-E	SLD1568-E
Description	15" TFT LCD, 1600/2000 nits LED backlight, 1024x768			
Screen size	15"			
Display area (mm)	304.1(H) x 228.1(V)			
Brightness	1600/2000 cd/m ²			
Resolution	1024x768			
Aspect ratio	4:3			
Contrast ratio	1000:1			
Pixel pitch (mm)	0.297 (H) x 0.297 (V)			
Pixel per inch (PPI)	85			
Viewing angle	160° (H), 160° (V)			
Color saturation (NTSC)	69%			
Display colors	16.7M			
Response time (Typical)	8ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	14w	17w		
Dimensions (mm)	326.5x253.5x12.5	326.5x253.5x12.5	350.5x253.5x31	326.5x253.5x31
Bezel size (U/B/L/R)	11.1/11.1/9.6/9.6	11.1/11.1/9.6/9.6	11.1/11.1/9.6/9.6	11.1/11.1/9.6/9.6
Weight (Net)	1kg	1.1kg	1.5kg	1.2kg
Mounting			VESA 75x75	VESA 75x75
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	-20°C ~ +70°C			
Storage temperature	-30°C ~ +80°C			
Product approval			CE, FCC	CE, FCC

Ordering Information

DLF1568-ENN-A21	15",1600nits,XGA,LID15A.1 in 1,V3
DLH1568-ENN-I21	15",1600nits,XGA,LID15A.AD6038GA,DC12V,1 in 1,V3
SLO1568-ENB-I21	15",1600nits,XGA,LID15A.AD6038G,O/B,DC12V,1 in 1,V3
SLD1568-ENB-I21	15",1600nits,XGA,LID15A.AD6038G,O/B,DC12V,1 in 1,V3