

1744-E

17" TFT LCD, 1000 nits LED backlight, 1280x1024



Sunlight
Readable



> 1000:1
ratio
High
Contrast



FULL
Low Power
Consumption



MTBF
70,000 Hrs

Key Features

- 17" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1280 x 1024
- Industry leading LED backlight
- Aspect ratio of 5:4
- High contrast ratio (1000:1)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF1744-E	DLH1744-E	DLO1744-E	DLD1744-E
Description	17" TFT LCD, 1000 nits LED backlight, 1280x1024			
Screen size	17"			
Display area (mm)	337.9(H) x 270.3(V)			
Brightness	1000 cd/m ²			
Resolution	1280x1024			
Aspect ratio	5:4			
Contrast ratio	1000:1			
Pixel pitch (mm)	0.264 (H) x 0.264 (V)			
Pixel per inch (PPI)	96			
Viewing angle	170° (H), 160° (V)			
Color saturation (NTSC)	83%			
Display colors	16.7M			
Response time (Typical)	5ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	35w	39w		
Dimensions (mm)	358.5x296.5x10.3	358.5x296.5x10.3	452.4x361.4x52.6	436x373x61.6
Bezel size (U/B/L/R)	11.18/11.18/8.39/8.39	11.18/11.18/8.39/8.39	11.18/11.18/8.39/8.39	11.18/11.18/8.39/8.39
Weight (Net)	2.16kg	2.26kg	4.93kg	6.33kg
Mounting			VESA 75x75,100x100	VESA 75x75,100x100
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	0°C ~ +50°C			
Storage temperature	-20°C ~ +60°C			
Product approval			CE, FCC	CE, FCC

Ordering Information

DLF1744-ENN-A22	17",1000nits,SXGA,LID17A.5 in 1,V03
DLH1744-ENN-I22	17",1000nits,SXGA,LID17A.AD6038GD,DC12V,5 in 1,V3
SLO1744-ENB-I21	17",1000nits,SXGA,LID17A.AD6038GD,O/B,DC 12V,V03
SLD1744-ENA-I21	17",1000nits,SXGA,LID17A.AD6038GD,O/F,DC 12V,V03