

1768-E

17" TFT LCD, 1600 nits LED backlight, 1280x1024



Sunlight Readable



High Contrast



Low Power Consumption



MTBF

Key Features

- 17" sunlight readable, high brightness (1600 nits)
- Resolutions: 1280 x 1024
- Industry leading LED backlight
- Aspect ratio of 5:4
- High contrast ratio (1000:1)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF1768-E	DLH1768-E	SLO1768-E	SLD1768-E
Description	17" TFT LCD, 1600 nits LED backlight, 1280x1024			
Screen size	17"			
Display area (mm)	337.9(H) x 270.3(V)			
Brightness	1600 cd/m ²			
Resolution	1280x1024			
Aspect ratio	5:4			
Contrast ratio	1000:1			
Pixel pitch (mm)	0.264 (H) x 0.264 (V)			
Pixel per inch (PPI)	96			
Viewing angle	170° (H), 160° (V)			
Color saturation (NTSC)	83%			
Display colors	16.7M			
Response time (Typical)	5ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	27w	32.5w		
Dimensions (mm)	358.5x296.5x20.5	358.5x296.5x20.5	389.7x298.3x36.2	358.5x298.3x35.9
Bezel size (U/B/L/R)	11.25/11.25/8.45/8.45	11.25/11.25/8.45/8.45	12.1/12.1/24/24	12.1/12.1/8.45/8.45
Weight (Net)	2kg	2.1kg	2.8kg	2.5kg
Mounting			VESA 75x75,100x100	VESA 75x75,100x100
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	0°C ~ +50°C			
Storage temperature	-20°C ~ +60°C			
Product approval			CE, FCC	CE, FCC

Ordering Information

DLF1768-ENN-A21	17",1600nits,SXGA,LID17A.5 in 1,V02
DLH1768-ENN-G21	17",1600nits,SXGA,LID17A.AD2662GD,DC12V,5 in 1,V02
SLO1768-ENB-G21	17",1600nits,SXGA,LID17A.AD2662GD,O/B,DC 12V,2 in 1.V02
SLD1768-ENB-G21	17",1600nits,SXGA,LID17A.AD2662GD,O/B,DC 12V,2 in 1.V02