

# 1825-E

18.5" TFT LCD, 1000 nits LED backlight, 1366x768



Sunlight Readable



High Contrast



Low Power Consumption



MTBF

## Key Features

- 18.5" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1366 x 768
- Industry leading LED backlight
- Aspect ratio of 16:9
- High contrast ratio (1250:1)
- Low power consumption
- BL MTBF: 70,000 hours

## Specifications

	DLF1825-E	DLH1825-E	SLO1825-E	SLD1825-E
Description	18.5" TFT LCD, 1000 nits LED backlight, 1366x768			
Screen size	18.5"			
Display area (mm)	409.8(H) x 230.4(V)			
Brightness	1000 cd/m <sup>2</sup>			
Resolution	1366x768			
Aspect ratio	16:9			
Contrast ratio	1250:1			
Pixel pitch (mm)	0.3 (H) x 0.3 (V)			
Pixel per inch (PPI)	84			
Viewing angle	170° (H), 160° (V)			
Color saturation (NTSC)	82%			
Display colors	16.7M			
Response time (Typical)	5ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	19w	24w		
Dimensions (mm)	430.4x254.6x13.35	430.4x254.6x13.35	475x330x60	475x330x61.6
Bezel size (U/B/L/R)	10.3/10.3/8.5/8.5	10.3/10.3/8.5/8.5	33.2/62.8/30.8/30.8	33.9/63.9/31.7/31.7
Weight (Net)	1.5kg	1.6kg	4kg	4.8kg
Mounting			VESA 75x75,100x100	VESA 75x75,100x100
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	0°C ~ +50°C			
Storage temperature	-20°C ~ +60°C			
Product approval			CE, FCC	CE, FCC

## Ordering Information

DLF1825-ENN-A11	18.5",1000nits,WXGA,LID18A,V2(5 in 1)
DLH1825-ENN-G11	18.5",1000nits,WXGA,LID18A.AD2662GD,DC 12V input.V2(5 in 1)
SLO1825-ENB-G11	18.5",1000nits,WXGA,LID18A.AD2662GD,O/B,DC 12V input.V2
SLD1825-ENA-G11	18.5",1000nits,WXGA,LID18A.AD2662GD,O/F,DC 12V input.V2