

# 1954-E

19" TFT LCD, 1000 nits LED backlight, 1280x1024



Sunlight Readable



> 1000:1 ratio  
High Contrast



Low Power Consumption



MTBF  
70,000 Hrs

## Key Features

- 19" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1280 x 1024
- Industry leading LED backlight
- High contrast ratio (1000:1)
- Low power consumption
- BL MTBF: 70,000 hours

## Specifications

	DLF1954-E	DLH1954-E	SLO1954-E	SLD1954-E
Description	19" TFT LCD, 1000 nits LED backlight, 1280x1024			
Screen size	19"			
Display area (mm)	376.3(H) x 301.0(V)			
Brightness	1000 cd/m <sup>2</sup>			
Resolution	1280x1024			
Aspect ratio	5:4			
Contrast ratio	1000:1			
Pixel pitch (mm)	0.294 (H) x 0.294 (V)			
Pixel per inch (PPI)	86			
Viewing angle	170° (H), 160° (V)			
Color saturation (NTSC)	80%			
Display colors	16.7M			
Response time (Typical)	5ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	21w	25w		
Dimensions (mm)	396x324x11.4	396x324x11.4	451x361.1x58	418.3x361.1x58
Bezel size (U/B/L/R)	9.5/9.5/8/8	9.5/9.5/8/8	20/38/36.4/36.4	20/38/20/20
Weight (Net)	2.6kg	2.7kg	5.5kg	5.35kg
Mounting			VESA 75x75,100x100	VESA 75x75,100x100
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	0°C ~ +50°C			
Storage temperature	-20°C ~ +60°C			
Product approval			CE, FCC	CE, FCC

## Ordering Information

DLF1954-ENN-A12	19",1000nits,SXGA,LID19A.5 in 1,V02
DLH1954-ENN-I12	19",1000nits,SXGA,LID19A.AD6038GD,DC 12V input,V02
SLO1954-ENB-I11	19",1000nits,SXGA,LID19A.AD6038G,O/B,DC 12V input,V02
SLD1954-ENA-I11	19",1000nits,SXGA,LID19A.AD6038G,O/F,DC 12V input.V02