

# 2118-E



21.5" TFT LCD, 1600 nits LED backlight, 1920x1080



Sunlight  
Readable



MTBF

100,000 Hrs



Low Power  
Consumption

## Key Features

- 21.5" sunlight readable, high brightness (1,600 nits)
- Resolutions: 1920 x 1080
- Industry leading LED backlight
- Aspect ratio of 16:9
- Low power consumption
- BL MTBF: 100,000 hours

## Specifications

	DLF2118-E	DLH2118-E	SLO2118-E	SLD2118-E
Description	21.5" TFT LCD, 1600 nits LED backlight, 1920x1080			
Screen size	21.5"			
Display area (mm)	476.6(H) x 268.1(V)			
Brightness	1600 cd/m <sup>2</sup>			
Resolution	1920x1080			
Aspect ratio	16:9			
Contrast ratio	900:1			
Pixel pitch (mm)	0.24825 (H) x 0.24825 (V)			
Pixel per inch (PPI)	102			
Viewing angle	170° (H), 160° (V)			
Color saturation (NTSC)	84%			
Display colors	16.7M			
Response time (Typical)	5ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	36w	41w		
Dimensions (mm)	497.6x292.2x13.35	497.6x292.2x13.35	530.2x294.6x36	500.2x294.6x35.5
Bezel size (U/B/L/R)	10.3/10.3/8.9/8.9	10.3/10.3/8.9/8.9	11.5/11.5/10.2/10.2	11.5/11.5/10.2/10.2
Weight (Net)	1.8kg	2.1kg	5.2kg	5kg
Mounting			VESA 75x75,100x100	VESA 75x75,100x100
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	0°C ~ +50°C			
Storage temperature	-20°C ~ +60°C			
Product approval			CE, FCC	CE, FCC

## Ordering Information

DLF2118-ENN-A01	21.5",1600nits,FHD,LID21A.5 in 1,V01
DLH2118-ENN-G01	21.5",1600nits,FHD,LID21A.AD2662GD,DC12V,5 in 1,V01
SLO2118-ENB-G01	21.5",1600nits,FHD,LID21A.AD2662GD,O/B,DC12V,3 in 1.V01
SLD2118-ENB-G01	21.5",1600nits,FHD,LID21A.AD2662GD,O/B,DC12V,3 in 1.V01