

2137-E


21.5" TFT LCD, 1400 nits LED backlight, 1920x1080



Sunlight Readable



High Contrast



Wide Viewing Angle



MTBF

Key Features

- 21.5" sunlight readable, high brightness (1,400 nits)
- Resolutions: 1920 x 1080
- Aspect ratio of 16:9
- Wide viewing angle of 178° (H), 178° (V)
- High contrast ratio (1300:1)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

	DLF2137-E	DLH2137-E	SLO2137-E	SLD2137-E
Description	21.5" TFT LCD, 1400 nits LED backlight, 1920x1080			
Screen size	21.5"			
Display area (mm)	476(H) x 267.7(V)			
Brightness	1400 cd/m ²			
Resolution	1920x1080			
Aspect ratio	16:9			
Contrast ratio	1300:1			
Pixel pitch (mm)	0.24795 (H) x 0.24795 (V)			
Pixel per inch (PPI)	102			
Viewing angle	178° (H), 178° (V)			
Color saturation (NTSC)	84%			
Display colors	16.7M			
Response time (Typical)	5ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	45w	50w		
Dimensions (mm)	497.6x292.2x13.35	497.6x292.2x13.35	545x370x60	545x370x61
Bezel size (U/B/L/R)	10.35/10.35/8.9/8.9	10.35/10.35/8.9/8.9	33.4/65.3/32.6/32.6	34.1/66.1/33.5/33.5
Weight (Net)	1.7kg	1.8kg	5.5kg	6.12kg
Mounting			VESA 75x75,100x100	VESA 75x75,100x100
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	0°C ~ +50°C			
Storage temperature	-20°C ~ +60°C			
Product approval			CE, FCC	CE, FCC

Ordering Information

DLF2137-ENN-A01	21.5",1400nits,FHD,LID21A.5-in-1,V1
DLH2137-ENN-G01	21.5",1400nits,FHD,LID21A.AD2662GD,DC 12V input.5-in-1,V1
SLO2137-ENB-G01	21.5",1400nits,FHD,LID21A.AD2662GD,O/B(5key)DC12V input.V1
SLD2137-ENB-G01	21.5",1400nits,FHD,LID21A.AD2662GD,O/B(5key)DC12V input.V1