

# 2415-E

24" TFT LCD, 1000 nits LED backlight, 1920x1080



Sunlight  
Readable



> 1000:1  
ratio  
High  
Contrast



FULL  
Low Power  
Consumption



MTBF  
70,000 Hrs

## Key Features

- 24" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1920 x 1080
- Industry leading LED backlight
- Aspect ratio of 16:9
- High contrast ratio (1000:1)
- Low power consumption
- BL MTBF: 70,000 hours

## Specifications

	DLF2415-E	DLH2415-E	SLO2415-E	SLD2415-E
Description	24" TFT LCD, 1000 nits LED backlight, 1920x1080			
Screen size	24"			
Display area (mm)	531.4(H) x 298.9(V)			
Brightness	1000 cd/m <sup>2</sup>			
Resolution	1920x1080			
Aspect ratio	16:9			
Contrast ratio	1000:1			
Pixel pitch (mm)	0.276 (H) x 0.276 (V)			
Pixel per inch (PPI)	91			
Viewing angle	170° (H), 160° (V)			
Color saturation (NTSC)	82%			
Display colors	16.7M			
Response time (Typical)	5ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	30w	38w		
Dimensions (mm)	555.9x323.3x14.6	555.9x323.3x14.6	586.4x325.6x36.5	558.4x325.6x36.5
Bezel size (U/B/L/R)	10.1/10.1/10.3/10.3	10.1/10.1/10.3/10.3	11.3/11.3/25.5/25.5	11.3/11.3/11.5/11.5
Weight (Net)	2.67kg	2.73kg	4.2kg	4kg
Mounting			VESA 75x75,100x100	VESA 75x75,100x100
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	0°C ~ +50°C			
Storage temperature	-20°C ~ +60°C			
Product approval			CE, FCC	CE, FCC

## Ordering Information

DLF2415-ENN-A01	24",1000nits,FHD(1920*1080).LID24A,V01
DLH2415-ENN-G01	24",1000nits,FHD(1920*1080).AD2662GD,LID24A01,V01
SLO2415-ENB-G01	24",1000nits,FHD,LID24A01.O/B,AD2662GD,V01
SLD2415-ENB-G01	24",1000nits,FHD,LID24A01.O/B,AD2662GD,V01