

2425-E

24" TFT LCD, 1000 nits LED backlight, 1920x1080



Sunlight Readable



> 1000:1 ratio
High Contrast



Wide Viewing Angle
178°



MTBF
70,000 Hrs

Key Features

- 24" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1920 x 1080
- Aspect ratio of 16:9
- Wide viewing angle of 178° (H), 178° (V)
- High contrast ratio (5000:1)
- Wide temperature (-20°C~70°C)
- BL MTBF: 100,000 hours

Specifications

	DLF2425-E	DLH2425-E	DLO2425-E	DLD2425-E
Description	24" TFT LCD, 1000 nits LED backlight, 1920x1080			
Screen size	24"			
Display area (mm)	531.4(H) x 298.9(V)			
Brightness	1000 cd/m ²			
Resolution	1920x1080			
Aspect ratio	16:9			
Contrast ratio	5000:1			
Pixel pitch (mm)	0.276 (H) x 0.276 (V)			
Pixel per inch (PPI)	91			
Viewing angle	178° (H), 178° (V)			
Color saturation (NTSC)	84%			
Display colors	16.7M			
Response time (Typical)	25ms			
Video interface	LVDS	VGA, DVI-D		
Input power		DC 12V		
Power consumption	30w	38w		
Dimensions (mm)	555.9x323.3x14.6	555.9x323.3x14.6	586.4x325.6x36.5	558.4x325.6x36.5
Bezel size (U/B/L/R)	10.1/10.1/10.3/10.3	10.1/10.1/10.3/10.3	11.3/11.3/25.5/25.5	11.3/11.3/11.5/11.5
Weight (Net)	2.67kg	2.73kg	4.2kg	4kg
Mounting			VESA 75x75,100x100	VESA 75x75,100x100
OSD key		4 keys (Power switch, menu, +, -)		
OSD control		Brightness, color, contrast, H/V position... etc		
Operating temperature	-20°C ~ +70°C			
Storage temperature	-30°C ~ +80°C			
Product approval			CE, FCC	

Ordering Information

DLF2425-ENN-A01	24",1000nits,FHD,LID24A02.V01
DLH2425-ENN-G01	24",1000nits,FHD,LID24A02.AD2662GD,V01
SLO2425-ENB-G01	24",1000nits,FHD,LID24A02.AD2662GD,O/B,DC12V input.V01
SLD2425-ENB-G01	24",1000nits,FHD,LID24A02.AD2662GD,O/B,DC12V input.V01