


3245-E

32" TFT LCD, 1200/1800 nits LED backlight, 1366x768



Key Features

- 32" sunlight readable, high brightness (1,200/1,800 nits)
- Resolutions: 1366 x 768
- Industry leading LED backlight
- Aspect ratio of 16:9
- Wide viewing angle of 176° (H), 176° (V)
- Low power consumption
- BL MTBF: 70,000 hours

Specifications

| | DLF3245-E | DLH3245-E | SLO3245-E | SLD3245-E |
|-------------------------|---|---------------------|-----------------------|-----------------------|
| Description | 32" TFT LCD, 1200/1800 nits LED backlight, 1366x768 | | | |
| Screen size | 32" | | | |
| Display area (mm) | 697.6(H) x 392.2(V) | | | |
| Brightness | 1200/1800 cd/m ² | | | |
| Resolution | 1366x768 | | | |
| Aspect ratio | 16:9 | | | |
| Contrast ratio | 5000:1 | | | |
| Pixel pitch (mm) | 0.51075 (H) x 0.51075 (V) | | | |
| Pixel per inch (PPI) | 50 | | | |
| Viewing angle | 176° (H), 176° (V) | | | |
| Color saturation (NTSC) | 74% | | | |
| Display colors | 16.7M | | | |
| Response time (Typical) | 7ms | | | |
| Video interface | LVDS | VGA, DVI-D, HDMI | | |
| Input power | AC 100~240V | | | |
| Power consumption | 60w/64w | 70w/74w | | |
| Dimensions (mm) | 737.6x426.2x16 | 737.6x426.2x16 | 781.4x428.8x53.5 | 740.2x428.8x53.5 |
| Bezel size (U/B/L/R) | 14.2/14.2/17.3/17.3 | 14.2/14.2/17.3/17.3 | 15.5/15.5/39.2/39.2 | 15.5/15.5/18.6/18.6 |
| Weight (Net) | 5.2kg | 5.4kg | 10kg | 9.8kg |
| Mounting | | | VESA 400x200, 200x100 | VESA 400x200, 200x100 |
| OSD key | 4 keys (Power switch, menu, +, -) | | | |
| OSD control | Brightness, color, contrast, H/V position... etc | | | |
| Operating temperature | 0°C ~ +50°C | | | |
| Storage temperature | -20°C ~ +60°C | | | |
| Product approval | | | CE, FCC | CE, FCC |

Ordering Information

| | |
|-----------------|---|
| DLF3245-ENN-A11 | 32",1200nits,WXGA,LID32A.V2(2 in1) |
| DLH3245-ENN-G11 | 32",1200nits,WXGA,LID32A.AD2662GD,AC100~240V,V2(2 in1) |
| SLO3245-ENB-G12 | 32",1200nits,WXGA,LID32A.AD2662GDHMMVAR,O/B.AC100~240V input,V02 |
| SLD3245-ENB-G13 | 32",1200nits,WXGA,LID32A.AD2662GD,O/B,LS,AC100~240V.V02 |
| DLF3245-ENN-A51 | 32",1800nits,WXGA,LID29A01.DC 12V input,V01,Standard.(2 in 1) |
| DLH3245-ENN-G51 | 32",1800nits,WXGA,LID29A01.AD2662GD,DC 12V input.V01,Standard(2 in 1) |
| SLO3245-ENB-G52 | 32",1800nits,WXGA,LID29A01.AD2662GDHM,O/B.AC100~240V,V01 |
| SLD3245-ENB-G51 | 32",1800nits,WXGA,LID29A01.AD2662GD,O/B,AC100~240V.V01 |