

# 3255-ANW

32" TFT LCD, 1000 nits LED backlight, MaxRGB, 1920x1080



## Key Features



- 32" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1920 x 1080
- MaxRGB (NTSC 94%)
- Wide viewing angle of 178° (H), 178° (V)
- High contrast ratio (6300:1)
- Low power consumption
- BL MTBF: 100,000 hours

## Specifications

|                         | DLF3255-ANW   | DLH3255-ANW                                      | DLD3255-ANW           |
|-------------------------|---|--|-----------------------|
| Description             | 32" TFT LCD, 1000 nits LED backlight, MaxRGB, 1920x1080 |  |                       |
| Screen size             | 32"   |  |                       |
| Display area (mm)       | 698.4(H) x 392.8(V)                                     |  |                       |
| Brightness              | 1000 cd/m <sup>2</sup>                                  |  |                       |
| Resolution              | 1920x1080   |  |                       |
| Aspect ratio            | 16:9  |  |                       |
| Contrast ratio          | 6300:1  |  |                       |
| Pixel pitch (mm)        | 0.3637 (H) x 0.3637 (V)                                 |  |                       |
| Pixel per inch (PPI)    | 68  |  |                       |
| Viewing angle           | 178° (H), 178° (V)                                      |  |                       |
| Color saturation (NTSC) | 94%   |  |                       |
| Display colors          | 16.7M   |  |                       |
| Response time (Typical) | 6.5ms   |  |                       |
| Video interface         | LVDS  | VGA, DVI-D, DP                                   |                       |
| Input power             |   | AC 100~240V                                      |                       |
| Power consumption       | 68w   | 71w  |                       |
| Dimensions (mm)         | 732.4x426.85x21.4                                       | 732.4x426.85x21.4                                | 735.4x429.7x59.6      |
| Bezel size (U/B/L/R)    | 14/14/14/14   | 14/14/14/14                                      | 15.5/15.5/15.5/15.5   |
| Weight (Net)            | 5.5kg   | 6.2kg  | 10.6kg                |
| Mounting                |   |  | VESA 100x100, 200x200 |
| OSD key                 |   | 4 keys (Power switch, menu, +, -)                |                       |
| OSD control             |   | Brightness, color, contrast, H/V position... etc |                       |
| Operating temperature   | 0°C ~ +50°C   |  |                       |
| Storage temperature     | -20°C ~ +60°C   |  |                       |
| Product approval        |   |  | CE, FCC               |

## Ordering Information

|                 |   |
|-----------------|---|
| DLF3255-ANW-A01 | 32",1000nits,FHD,MaxRGB,LID32A,2in1,V1                      |
| DLH3255-ANW-I01 | 32",1000nits,FHD,MaxRGB,LID32A.AD6038GDP,AC100~240V,2in1,V1 |
| DLD3255-ANW-I01 | 32",1000nits,FHD,MaxRGB,LID32A.AD6038GDP,O/B,AC100~240V,V1  |
|                 |   |
|                 |   |
|                 |   |
|                 |   |