

3585-INK



TAXI

35.8" Resizing LCD, 1000 nits LED backlight, MaxRGB, 3840x1076



Key Features



Sunlight Readable



Resizing Display



MaxRGB



4K2K

- 35.8" resizing LCD
- Resizing display (aspect ratio of 16:4.5)
- Sunlight readable, high brightness (1,000 nits)
- Resolutions: 3840 x 1076
- MaxRGB (NTSC 94%)
- Wide viewing angle of 178° (H), 178° (V)
- BL MTBF: 100,000 hours

Specifications

	SSF3585-INK	SSH3585-INK	SSD3585-INK
Description	35.8" Resizing LCD, 1000 nits LED backlight, MaxRGB, 3840x1076		
Screen size	35.8"		
Display area (mm)	878.1(H) x 241.7(V)		
Brightness	1000 cd/m ²		
Resolution	3840x1076		
Aspect ratio	16:4.5		
Contrast ratio	3400:1		
Pixel pitch (mm)	0.2247 (H) x 0.2247 (V)		
Pixel per inch (PPI)	111		
Viewing angle	178° (H), 178° (V)		
Color saturation (NTSC)	94%		
Display colors	1.07G		
Response time (Typical)	8.5ms		
Video interface	V-by-One	VGA, DVI-D, HDMI, DP	
Input power		AC 100~240V	
Power consumption	83w	88w	
Dimensions (mm)	899.4x270.7x18.8	899.4x270.7x18.8	902x273.3x62.2
Bezel size (U/B/L/R)	12/12/8.6/8.6	12/12/8.6/8.6	13.3/13.3/9.9/9.9
Weight (Net)	4.5kg	5kg	9.2kg
Mounting			VESA 300x75
OSD key		5 keys (Power switch, menu, +, -, Exit)	
OSD control		Brightness, color, contrast, H/V position... etc	
Operating temperature	0°C ~ +50°C		
Storage temperature	-20°C ~ +60°C		
Product approval			CE, FCC

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Ordering Information

SSF3585-INK-A01	35.8",1000nits,3840x1076,MaxRGB,LID35A,3in1,V1
SSH3585-INK-M01	35.8",1000nits,3840x1076,MaxRGB,AD9131DHP,AC100~240V,3in1,V1
SSD3585-INK-M01	35.8",1000nits,3840x1076,MaxRGB,AD9131DHP,O/B,Speaker*2,AC100~240V,2in1,V1