

4235-E

42" TFT LCD, 1000 nits LED backlight, 1920x1080



Sunlight Readable



Wide Viewing Angle



> 1000:1 ratio
High Contrast



MTBF
70,000 Hrs

Key Features

- 42" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1920 x 1080
- Aspect ratio of 16:9
- Wide viewing angle of 178° (H), 178° (V)
- High contrast ratio (1200:1)
- Low power consumption
- BL MTBF 70,000 hours

Specifications

	DLF4235-E	DLH4235-E	SLO4235-E	SLD4235-E
Description	42" TFT LCD, 1000 nits LED backlight, 1920x1080			
Screen size	42"			
Display area (mm)	927.9(H) x 521.9(V)			
Brightness	1000 cd/m ²			
Resolution	1920x1080			
Aspect ratio	16:9			
Contrast ratio	1200:1			
Pixel pitch (mm)	0.4833 (H) x 0.4833 (V)			
Pixel per inch (PPI)	53			
Viewing angle	178° (H), 178° (V)			
Color saturation (NTSC)	75%			
Display colors	16.7M			
Response time (Typical)	8ms			
Video interface	LVDS	VGA, DVI-D		
Input power	AC 100~240V			
Power consumption	96w	119w		
Dimensions (mm)	965x557x24	965x557x24	1018x560x65	968x560x65
Bezel size (U/B/L/R)	13/13/15/15	13/13/15/15	14.5/14.5/20.75/20.75	14.5/14.5/16.5/16.5
Weight (Net)	9.5kg	9.5kg	17.5kg	17kg
Mounting			VESA 400x100, 200x100	VESA 400x100, 200x100
OSD key	4 keys (Power switch, menu, +, -)			
OSD control	Brightness, color, contrast, H/V position... etc			
Operating temperature	0°C ~ +50°C			
Storage temperature	-20°C ~ +60°C			
Product approval			CE, FCC	CE, FCC

Ordering Information

DLF4235-ENN-A11	42",1000nits,FHD,LID42A.3 in 1,V02
DLH4235-ENN-G11	42",1000nits,FHD,LID42A.AD2662GD,AC100~240V,3 in 1,V02
SLO4235-ENB-G11	42",1000nits,FHD,LID42.AD2662GD,O/B,AC100~240V.V02
SLD4235-ENB-G11	42",1000nits,FHD,LID42A.AD2662GD,O/B,AC100~240V.V02