

4309-ANK

43" TFT LCD, 1400 nits LED backlight, MaxRGB, 3840x2160



Key Features

- 43" sunlight readable, high brightness (1,400 nits)
- Resolutions: 3840 x 2160
- MaxRGB (NTSC 94%)
- Wide viewing angle of 178° (H), 178° (V)
- High contrast ratio (1800:1)
- Low power consumption
- BL MTBF: 100,000 hours

Specifications

	DLF4309-ANK	DLH4309-ANK	DLD4309-ANK
Description	43" TFT LCD, 1400 nits LED backlight, MaxRGB, 3840x2160		
Screen size	43"		
Display area (mm)	941.1(H) x 529.4(V)		
Brightness	1400 cd/m ²		
Resolution	3840x2160		
Aspect ratio	16:9		
Contrast ratio	5600:1		
Pixel pitch (mm)	0.49005 (H) x 0.49005 (V)		
Pixel per inch (PPI)	102		
Viewing angle	178° (H), 178° (V)		
Color saturation (NTSC)	94%		
Display colors	1.07G		
Response time (Typical)	8ms		
Video interface	V-by-One	DVI-D, HDMI, DP	
Input power	AC 100~240V		
Power consumption	169w	174w	
Dimensions (mm)	968.2x556.4x44.8	968.2x556.4x44.8	971.6x559.8x96
Bezel size (U/B/L/R)	11.5/11.5/11.6/11.6	11.5/11.5/11.6/11.6	13.2/13.2/13.3/13.3
Weight (Net)	11kg	11.5kg	21kg
Mounting			VESA 400x100
OSD key	5 keys (Power switch, menu, +, -, Exit)		
OSD control	Brightness, color, contrast, H/V position... etc		
Operating temperature	0°C ~ +50°C		
Storage temperature	-20°C ~ +60°C		
Product approval			CE, FCC

Ordering Information

DLF4309-ANK-A01	43",1400nits,UHD,MaxRGB,LID43B,3in1,V1
DLH4309-ANK-M01	43",1400nits,UHD,MaxRGB,LID43B,AD9131DHP,AC100~240V,3in1,V1
DLD4309-ANK-M01	43",1400nits,UHD,MaxRGB,LID43B,AD9131GDHP,O/B,Speaker*2,AC100~240V,2in1,V1