

# 4350-I

43.5" Resizing LCD, 2000 nits LED backlight, 1920x268



TAXI



## Key Features

- 43.5" resizing LCD
- Resizing display (aspect ratio of 16 : 2.2)
- Sunlight readable, high brightness (2,000 nits)
- Resolutions: 1920 x 268
- Wide view angle of 176° (H), 176° (V)
- Low power consumption
- BL MTBF: 100,000 hours



Sunlight Readable



Resizing Display



Wide Viewing Angle



MTBF

100,000 Hrs

## Specifications

	SSF4350-I	SSH4350-I	SSD4350-I
Description	43.5" Resizing LCD, 2000 nits LED backlight, 1920x268		
Screen size	43.5"		
Display area (mm)	1095.84(H) x 153 (V)		
Brightness	2000 cd/m <sup>2</sup>		
Resolution	1920x268		
Aspect ratio	16:2.2		
Contrast ratio	7000:1		
Pixel pitch (mm)	0.5708 (H) x 0.5708 (V)		
Pixel per inch (PPI)	44		
Viewing angle	176° (H), 176° (V)		
Color saturation (NTSC)	79%		
Display colors	16.7M		
Response time (Typical)	9.5ms		
Video interface	LVDS	VGA, DVI-D, HDMI, DP	
Input power		AC 100~240V	
Power consumption	55w	60w	
Dimensions (mm)	1121.7x184.8x21.6	1121.7x184.8x21.6	1124.3x187.4x64.6
Bezel size (U/B/L/R)	13.3/13.3/10.9/10.9	13.3/13.3/10.9/10.9	14.6/14.6/12.2/12.2
Weight (Net)	4.8kg	4.8kg	8.6kg
Mounting			VESA 300x75
OSD key		4 keys (Power switch, menu, +, -)	
OSD control		Brightness, color, contrast, H/V position... etc	
Operating temperature	0°C ~ +50°C		
Storage temperature	-20°C ~ +60°C		
Product approval			CE, FCC

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

## Ordering Information

SSF4350-INN-A01	43.5",2000nits,1920*268,LID43A,3in1,V1
SSH4350-INN-J01	43.5",2000nits,1920*268,LID43A,AD5827GDHP,DC12V,3in1,V1
SSD4350-INB-J01	43.5",2000nits,1920*268,LID43A,AD5827GDHP,O/B,speaker*2,DC12V,2in1,V1