

# 4355-INK

43.5" Resizing LCD, 1000 nits LED backlight, MaxRGB, 3840x536



TAXI



## Key Features

- 43.5" resizing LCD
- Resizing display (aspect ratio of 16 : 2.2)
- Sunlight readable, high brightness (1,000 nits)
- Resolutions: 3840 x 536
- MaxRGB (NTSC 95%)
- Wide view angle of 178° (H), 178° (V)
- BL MTBF: 100,000 hours



Sunlight Readable



Resizing Display



MaxRGB



4K2K

## Specifications

	SSF4355-INK	SSH4355-INK	SSD4355-INK
Description	43.5" Resizing LCD, 1000 nits LED backlight, MaxRGB, 3840x536		
Screen size	43.5"		
Display area (mm)	1095.8(H) x 153 (V)		
Brightness	1000 cd/m <sup>2</sup>		
Resolution	3840x536		
Aspect ratio	16:2.2		
Contrast ratio	7700:1		
Pixel pitch (mm)	0.2854 (H) x 0.2854 (V)		
Pixel per inch (PPI)	89		
Viewing angle	178° (H), 178° (V)		
Color saturation (NTSC)	95%		
Display colors	1.07G		
Response time (Typical)	9.5ms		
Video interface	V-by-One	VGA, DVI-D, HDMI, DP	
Input power	AC 100~240V		
Power consumption	74w	79w	
Dimensions (mm)	1121.7x184.8x21.6	1121.7x184.8x21.6	1124.3x187.4x64.6
Bezel size (U/B/L/R)	13.3/13.3/10.9/10.9	13.3/13.3/10.9/10.9	14.6/14.6/12.2/12.2
Weight (Net)	4.8kg	4.8kg	8.6kg
Mounting			VESA 300x75
OSD key	5 keys (Power switch, menu, +, -, Exit)		
OSD control	Brightness, color, contrast, H/V position... etc		
Operating temperature	0°C ~ +50°C		
Storage temperature	-20°C ~ +60°C		
Product approval			CE, FCC

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

## Ordering Information

SSF4355-INK-A01	43.5",1000nits,3840x536,MaxRGB,LID43A,3in1,V1
SSH4355-INK-M01	43.5",1000nits,3840x536,LID43A,AD9131GDHP,AC100~240V,3in1,V1
SSD4355-INK-M01	43.5",1000nits,3840x536,LID43A,AD9131GDHP,O/B,Speaker*2,AC100~240V,2in1,V1