

4848-A

48.4" Resizing LCD, 1600 nits LED backlight, 1920x358



TAXI



Sunlight Readable



Resizing Display



Wide Viewing Angle



MTBF

70,000 Hrs



Key Features

- 48.4" resizing LCD
- Resizing display (aspect ratio of 16:3)
- Sunlight readable, high brightness (1,600 nits)
- Resolutions: 1920 x 358
- Wide view angle of 178° (H), 178° (V)
- BL MTBF: 70,000 hours

Specifications

	SSF4848-A	SSH4848-A	SSD4848-A
Description	48.4" Resizing LCD, 1600 nits LED backlight, 1920x358		
Screen size	48.4"		
Display area (mm)	1209.6(H) x 225.5(V)		
Brightness	1600 cd/m ²		
Resolution	1920x358		
Aspect ratio	16:3		
Contrast ratio	8000:1		
Pixel pitch (mm)	0.63 (H) x 0.63 (V)		
Pixel per inch (PPI)	40		
Viewing angle	178° (H), 178° (V)		
Color saturation (NTSC)	80%		
Display colors	16.7M		
Response time (Typical)	8.5ms		
Video interface	LVDS	VGA, DVI-D, HDMI	
Input power		AC 100~240V	
Power consumption	78w	83w	
Dimensions (mm)	1244.6x264.9x27.6	1244.6x264.9x27.6	1247.5x268x66.6
Bezel size (U/B/L/R)	17.7/17.7/15.5/15.5	17.7/17.7/15.5/15.5	19.3/19.3/17/17
Weight (Net)	9kg	9kg	11.5kg
Mounting			VESA 400x100, 800x100
OSD key		4 keys (Power switch, menu, +, -)	
OSD control		Brightness, color, contrast, H/V position... etc	
Operating temperature	0°C ~ +50°C		
Storage temperature	-20°C ~ +60°C		
Product approval			CE, FCC

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Ordering Information

SSF4848-ANN-A02	48.4",1600nits,1920*358,LID48A.2 in 1,V01
SSH4848-ANN-G02	48.4",1600nits,1920*358,LID48A.AD2662GDHMVAR,speaker*2.AC100~240V,2 in 1,V01
SSD4848-ANB-G01	48.4",1600nits,1920*358,LID48A.AD2662GDHMVAR,speaker*2.O/B,AC100~240V,V01